



418.00 EUR  
incl. 19% VAT, plus [shipping](#)

- INTEL® Pine Trail-D Processor D525 + ICH8M Chipset
- Support 1 \* DDR3 800/667MHz Single CH up to 4GB
- Support 1 \* Serial ATAII (3Gb/s) Device
- Support 8x Gigabit LAN
- Support VGA Output
- Equipped with 802.11 b/g/n WiFi card & Internal Antenna (JBC373F38W-525-B only)
- Support 2 \* COM ports
- Support 2.5" SATA HDD drive bay
- Support 2 \* Mini PCI-E socket (one shared with mSATA)
- Provide CF card socket (Support CF or CF SATA card)
- Provides Wall mount bracket & VESA mount (Optional)

|                                  |                                                                                                                                            |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model No</b>                  | <b>JBC373F38-525-B / JBC373F38W-525-B</b>                                                                                                  |
| <b>Motherboard Specification</b> |                                                                                                                                            |
| <b>CPU</b>                       | INTEL® Pine Trail-D Processor D525                                                                                                         |
| <b>Chipset</b>                   | INTEL® ICH8M Express chipset                                                                                                               |
| <b>Memory</b>                    | 1 * DDR3 800/667MHz Single CH SO-DIMM up to 4GB                                                                                            |
| <b>Expansion Slots</b>           | 2 * Mini PCI-E                                                                                                                             |
| <b>LAN</b>                       | 8 * Realtek RTL8111EVL PCI-E Gigabit Ethernet LAN                                                                                          |
| <b>Storage</b>                   | 1 * Serial ATA2 3Gb/s connector<br>1 * CF card socket (Support CF or CF SATA card)<br>1 * mSATA socket (Shared with one Mini PCI-E socket) |
| <b>BIOS</b>                      | AMI 16MB SMT Flash ROM                                                                                                                     |
| <b>Form Factor</b>               | 3.5" SBC (148mm x 102mm)                                                                                                                   |
| <b>Barebone Specification</b>    |                                                                                                                                            |
| <b>Product size</b>              | 180 (W) * 142 (D) * 48 (H) mm                                                                                                              |
| <b>Specs Devices</b>             | 1 x 2.5" HDD Drive Bay ( <b>Only support SATA 2.5" HDD</b> )                                                                               |
| <b>Colors</b>                    | Black                                                                                                                                      |
| <b>Front I/O Port</b>            | 1 * Power button & 1 * Reset button<br>1 * Power LED & 1 * HDD LED<br>2 * USB 2.0 ports<br>4 * NIC LED's<br>4 * LAN ports                  |

|                      |                                                                                                                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Rear I/O Port</b> | 2 * USB 2.0 ports 1 * 12V DC jack<br>4 * RJ-45 port(Gigabit LAN) 1 * Kensington hole<br>2 * Antenna holes 1 * VGA & 1 * COM port                                                              |
| <b>Power supply</b>  | +12V DC-IN Power                                                                                                                                                                              |
| <b>Accessory</b>     | 60W AC-DC Adapter x 1 Power Cord x 1<br>CD x 1 Manual x 1<br>COM cable x 1 WI-FI antenna * 1 ■ <b>JBC373F38W-525-B only</b> ■<br>Wall Mount Bracket x 2 LCD VESA Mount Bracket x 1 (Optional) |
| <b>Application</b>   | Networking Appliance, Set Top Box, Thin Client                                                                                                                                                |
| <b>Packing</b>       | Color Box Dimension ■ 250(W) x 118 (D) x 295 (H) mm<br>Gross Weight ■ 2.78KG Net Weight ■ 1.43KG                                                                                              |