




209.00 EUR

incl. 19% VAT, plus [shipping](#)

- INTEL® Cedar Trail-D Processor D2700 + NM10 Chipset
- Support 2 * DDR3 800/1067MHz Single CH up to 4GB
- Support DirectX 9 Graphics up to 640MHz
- Support 2 * Serial ATAII (3Gb/s) & 2 * Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- Supports 2 * Realtek RT8111EVL Gigabit LAN
- 1 * 24 bits Single Channel LVDS header
- Support Watch dog Technology
- Compliance with ERP standard
- Mini-ITX Form Factor(170mm x 170mm)
- Support Daughter board Expansion
- **CPU**
 - INTEL® Cedar Trail-D Processor D2700 CPU
- **Chipset**
 - INTEL®NM10 Express chipset
- **Memory**
 - 2 * DDR3 800/1067MHz Single CH up to 4GB
- **Expansion Slots**
 - 1 * PCI slot
 - 1 * Mini PCI-E socket
- **Storage**
 - 2 * Serial ATAII 3Gb/s + 2 * Serial ATAIII 6Gb/s connectors
- **Audio**
 - Realtek ALC662 HD Audio Code with 6-Channel
- **Ethernet LAN**
 - 2 * Realtek RTL8111EVL PCI-E Gigabit Ethernet LAN

- **USB**
 - Embedded 7 * USB 2.0/1.1
- **Special Features**
 - Support ACPI S3
 - Support CPU Smart FAN & DC FAN
 - Onboard 24-bits Single Channel LVDS connector
- **LVDS**
- **Rear Panel I / O**
 - 4 * USB 2.0/1.1 ports
 - 1 * PS/2 KB/MS connector
 - 2 * RJ-45 port
 - 1 * Audio port (Line-in, MIC and Line-out)
 - 1 * VGA port
 - 1 * HDMI port
 - 1 * COM port
- **Internal I / O**
 - 2 * USB 2.0/1.1 headers for 3 USB 2.0 ports
 - CPU / Chassis Fan connectors
 - 1 * 24-pin ATX Power connector
 - 1 * COM header (for RS-232/422/485)
 - 1 * chassis intrusion header
 - 1 * 2-pin SPDIF out header
 - 1 * Parallel header
 - 1 * GPIO header
- **BIOS**
 - AMI 16MB DIP-SPI Flash ROM
- **Functional**
 - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation, Financial Application
- **Packing**
 - Color Box Dimension ■ 200(W) x 200(D) x 70(H)mm
 - Cases Gross Weight ■ 15.4KGS
 - Cases Net Weight ■ 10.3KGS
 - 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm
- **Certificate**
 - CE, FCC, RoHS
- **Temperature**
 - Operating within 0~60 centigrade (**Suggest to use system FAN**)
 - Storage within -20-85 centigrade
- **Form Factor**
 - Mini ITX Form Factor(170mmx170mm)

Product Accessories

- COM cable
- Manual
- CD
- SATA cable
- I/O shield
- 1x fan