

469.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake Celeron 3855U/3955U SoC Processor (Default)
- 1\* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 GB
- 4/6\* 10/100/1000 Base-TX Ethernet Ports
- 1\* Full size Mini-SATA Socket (SATA + USB Signal)
- 2\* Mini PCIe Slots (1\* full size & 1\* half size)
- 1\* SIM card holder
- Supports on board TPM1.2/2.0 (option)
- 1\* RS232 Console, 2\* USB3.0
- Supports Antenna up to 4

|                 |                                                                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Processor       | – Intel® Skylake Celeron 3855U/3955U SoC Processor (Default)                                                                                       |
| Chipset         | – SoC Integrated                                                                                                                                   |
| Memory          | – 1 * SO-DIMM DDR4-2133MHz up to 16GB                                                                                                              |
| Storage         | – 1 * 2.5" SATA3 6Gb/s internal drive bay<br>– 1 * full size mSATA                                                                                 |
| Network         | – 1 * Intel® i219LM GbE & 3 * Intel® i225V (Default on board)<br>– 2 * Intel® i350 GbE (Expansion by request)                                      |
| Expansion slot  | – 1 * half size Mini PCIe slot (for WiFi expansion)<br>– 1 * full size Mini PCIe slot with 1 * SIM card holder                                     |
| Front Panel I/O | – 1 * Power LED , 1 * HDD LED<br>– 2 * USB 3.0<br>– 1 * COM<br>– 4 * RJ45 (3 * i225V + 1 * i219LM)<br>– 2 * RJ45 (Intel i350 / option)             |
| Rear Panel I/O  | – 1 * Power switch<br>– 1 * HDMI (Max. resolution:4096 x 2304@24Hz)<br>– 1 * COM or GPIO (Option)<br>– 1 * DC-in jack<br>– Support Antenna up to 4 |

|                |                                                                                                                                                                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Other Features | <ul style="list-style-type: none"> <li>– TPM1.2 or TPM2.0 (On board option)</li> <li>– Reserve internal pin header 8-bit Digital I/O interface (4-in /4-out)</li> <li>– 0~255 segments by software programmable</li> <li>– 1 * System FAN</li> </ul> |
| Power Source   | – FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6                                                                                                                                                                                             |
| Compliance     | – CE, FCC, LVD, RoHS                                                                                                                                                                                                                                 |
| Safety         | <ul style="list-style-type: none"> <li>– Vibration test: N.C</li> <li>– Shock test: N.C</li> </ul>                                                                                                                                                   |
| Temperature    | <ul style="list-style-type: none"> <li>– Operating Temperature: 0 ~ 50° C</li> <li>– Storage Temperature: -10 ~ 70° C</li> </ul>                                                                                                                     |
| Dimensions     | – 232 (W) x 152 (D) x 44 (H) mm                                                                                                                                                                                                                      |
| Packing        | <ul style="list-style-type: none"> <li>– Net Weight: 1.8KG</li> <li>– Gross Weight: 2.8KG</li> <li>– Color Box dimension: 250 (W) * 115 (D) * 365 (H) mm</li> </ul>                                                                                  |
| OS Support     | – 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux                                                                                                                                                                                    |
| Warranty       | – 1 Year limited warranty                                                                                                                                                                                                                            |