429.00 EUR
incl. 19% VAT, plus shipping

- Intel® Skylake Celeron 3855U/3955U SoC Processor (Default)
- 1* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 GB
- 4/6* 10/100/1000 Base-TX Ethernet Ports
- 1* Full size Mini-SATA Socket (SATA + USB Signal)
- 2* Mini PCIe Slots (1* full size & 1* half size)
- 1* SIM card holder
- Supports on board TPM1.2/2.0 (option)
- 1* RS232 Console, 2* USB3.0
- Supports Antenna up to 4

Processor	– Intel® Skylake Celeron 3855U/3955U SoC Processor (Default)
Chipset	– SoC Integrated
Memory	– 1 * SO-DIMM DDR4-2133MHz up to 16GB
Storage	– 1 * 2.5” SATA3 6Gb/s internal drive bay – 1 * full size mSATA
Network	– 1 * Intel® i219LM GbE & 3 * Intel® i211AT (Default on board) – 2 * Intel® i350 GbE (Expansion by request)
Expansion slot	– 1 * half size Mini PCIe slot (for WiFi expansion) – 1 * full size Mini PCIe slot with 1 * SIM card holder
Front Panel I/O	– 1 * Power LED , 1 * HDD LED – 2 * USB 3.0 – 1 * COM – 4 * RJ45 (3 * i211AT + 1 * i219LM) – 2 * RJ45 (Intel i350 / option)
Rear Panel I/O	– 1 * Power switch – 1 * HDMI (Max. resolution:4096 x 2304@24Hz) – 1 * COM or GPIO (Option) – 1 * DC-in jack – Support Antenna up to 4

Other Features	– TPM1.2 or TPM2.0 (On board option) – Reserve internal pin header 8-bit Digital I/O interface (4-in /4-out) – 0~255 segments by software programmable – 1 * System FAN
Power Source	– FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6
Compliance	– CE, FCC, LVD, RoHS
Safety	– Vibration test: N.C – Shock test: N.C
Temperature	– Operating Temperature: 0 ~ 50° C – Storage Temperature: -10 ~ 70° C
Dimensions	– 232 (W) x 152 (D) x 44 (H) mm
Packing	– Net Weight: 1.8KG – Gross Weight: 2.8KG – Color Box dimension: 250 (W) * 115 (D) * 365 (H) mm
OS Support	– 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux
Warranty	– 1 Year limited warranty