



1369.00 EUR

incl. 19% VAT, plus [shipping](#)

- Ultra 7 155U !
- Intel PTT (fTPM) !
- 2 x 2.5GbE !
- Fanless !



- Powered with with Intel® Core™ Ultra 7 155U
- High-Speed Networking: 2 x 2.5GbE for fast and reliable connectivity
- 4K Display: Supports HDMI® 2.0b (4096 x 2160@60Hz) for high-resolution output
- Flexible Storage: 1 x SATA III, 1 x M.2 E-Key, 1 x B+M Key paired with 1 x Nano SIM Slot
- Comprehensive I/O: 4 x RS485/422/232, 3 x USB 3.2 Gen 2, 4 x USB 2.0, 2 x RJ45
- Versatile Mounting: Supports desktop, wall mount, and DIN rail installation

#### SYSTEM

##### MB FORM FACTOR

##### CPU

##### CHIPSET

##### MEMORY

##### BIOS

##### WAKE ON LAN

##### WATCHDOG TIMER

##### SECURITY

##### RTC BATTERY

##### OS SUPPORT

##### POWER

##### POWER REQUIREMENT

##### POWER ON MODE

##### DISPLAY

##### GPU

##### Performance

Onboard Intel® Core™ Ultra 7 Processor 155U (Formerly Meteor Lake, TDP 15W)

Intel® SoC

2 x DDR5 5600MT/s, Dual Channel SO-DIMM, up to 96GB

UEFI

Yes

255 Levels

dTPM

Lithium Battery

Windows® 11 (64bit)

Windows® 10 (64bit)

Linux

DC-in 12~36V

90W Adapter: AC90~240V, DC19V/4.7A

AT / ATX (Default) Mode

Intel® Graphics

|                             |                                                                                                                                                                                                  |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type C DP                   | 1 x Type C DP1.4 (Max Resolution: 4096 x 2160@60Hz)                                                                                                                                              |
| DP                          | 2 x DP1.4 (Max Resolution: 4096 x 2160@60Hz)                                                                                                                                                     |
| HDMI                        | 2 x HDMI 2.0b (Max Resolution: 4096 x 2160@60Hz)                                                                                                                                                 |
| MULTIPLE DISPLAY            | Support 3 Displays                                                                                                                                                                               |
| AUDIO                       |                                                                                                                                                                                                  |
| CODEC                       | Realtek Audio Codec                                                                                                                                                                              |
| AMPLIFIER                   | 3W                                                                                                                                                                                               |
| LAN                         |                                                                                                                                                                                                  |
| ETHERNET                    | 1 x RJ45 for Intel® I226-V 2.5GbE<br>1 x RJ45 for Intel® I226-LM 2.5GbE                                                                                                                          |
| SYSTEM I/O                  |                                                                                                                                                                                                  |
|                             | 4 x Antenna Holes<br>1 x DC-in<br>1 x HDMI® 2.0b<br>1 x DP<br>3 x USB 3.2 Gen 2<br>1 x USB 3.2 Gen 1 Type-C<br>2 x RJ45<br>1 x GND Hold<br>1 x Power Button<br>1 x Reset Button<br>1 x Power LED |
| REAR PANEL I/O              | 1 x HDD LED<br>4 x USB 2.0<br>4 x RS-232/422/485<br>2 x Antenna Holes                                                                                                                            |
| FRONT PANEL I/O             |                                                                                                                                                                                                  |
| EXPANSION                   |                                                                                                                                                                                                  |
| M.2                         | 1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVi<br>1 x B-Key 3042/3052 (USB 3.2/PCIe 3.0 x2)<br>1 x M-Key 2242/2280 (PCIe 4.0 x4 / SATA III) Support NVMe<br>1 x Nano SIM Card Slot            |
| SIM                         |                                                                                                                                                                                                  |
| MECHANICAL                  |                                                                                                                                                                                                  |
| MOUNTING                    | Desktop, Wallmount, Din Rail                                                                                                                                                                     |
| DIMENSIONS (W x D x H)      | 185.0 (W) x 142.0 (D) x 61.0 (H) mm (7.28" x 5.6" x 2.4")                                                                                                                                        |
| NET WEIGHT                  | 3.5 kg                                                                                                                                                                                           |
| ENVIRONMENT & CERTIFICATION |                                                                                                                                                                                                  |
| OPERATING TEMPERATURE       | -20°C ~ 60°C (-4°F ~ 140°F)                                                                                                                                                                      |
| STORAGE TEMPERATURE         | -40°C ~ 85°C (-40°F ~ 185°F)                                                                                                                                                                     |
| OPERATING HUMIDITY          | 10 ~ 90% Relative Humidity, Non-condensing                                                                                                                                                       |
| CERTIFICATION               | CE/FCC Class A<br>LVD                                                                                                                                                                            |