



639.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel J6412 !
- 6 x 2.5GbE !
- 4 x PoE LAN !
- Fanless !

- Fanless embedded box PC with Intel® Celeron® Processor J Series (formerly Elkhart Lake)
- 6 x Intel® 2.5GbE LAN, with LAN3/4/5/6 supporting PoE according to IEEE 802.3af/at
- 4K Display: 1 x HDMI with a maximum resolution of 2560 x 1600@60Hz
- Memory: 1 x DDR4 3200/2933MHz SO-DIMM, up to 32GB
- Storage options: 1 x M.2 M-Key 2242 with SATA interface and 1 x 2.5-inch SATA 6Gb/s drive bay
- Comprehensive I/O: 3 x RS232, 1 x RS232/422/485, 2 x USB 3.2 Gen.1 and 6 x RJ45

SYSTEM

CPU

Intel® Celeron® Processor J Series (formerly Elkhart Lake)

CHIPSET

Intel® J6412 (TDP 10W)

SYSTEM MEMORY

1 x DDR4 3200/2933MHz up to 32GB

OS SUPPORT

Windows® 10

Windows® 11

Linux

POWER

MB: 12V DC-in

POWER REQUIREMENT

PoE: 9~36V DC-in for PoE

Adapter: AC100~240V / DC12V_7.5A_90W

DISPLAY

DISPLAY INTERFACE

1 x HDMI (Max Resolution: 2560 x 1600@60Hz)

LAN

ETHERNET

6 x Intel® 2.5 GbE LAN i225-V (or Intel® I226-V)

LAN3/4/5/6 PoE LAN, Support IEEE 802.3af/at (Total Max 100W)

SYSTEM I/O

FRONT I/O

-

REAR I/O

1 x Phoenix terminal block System (12V DC-in)
1 x HDMI (Max Resolution: 2560 x 1600@60Hz)
4 x COM (COM1: RS232-RJ45, COM2: RS232/422/485, COM3/4:
RS232)
1 x Power Button
1 x GND Hold
1 x Power LED
1 x HDD LED
2 x USB3.2 Gen.1
6 x RJ45

INDICATOR

1 x Phoenix terminal block for PoE (9~36V DC-in)
1 x Power LED
1 x HDD LED

STORAGE**STORAGE DEVICE**

1 x M.2 M key (2242, SATA Interface)
1 x 2.5" SATA 6Gb/s internal drive bay (height ?10mm)

MECHANICAL**MOUNTING**

Desktop, Wallmount

DIMENSIONS (W x H x D)

200.0 (W) x 180.4 (D) x 59.5 (H) mm (6.0" x 5.41" x 1.78")

ENVIRONMENT & CERTIFICATION**OPERATING TEMPERATURE**

-10°C ~ 50°C (14°F ~122°F)
(Under the condition of using M.2 interface SSD)

STORAGE TEMPERATURE

-20°C ~ 60°C (-4°F ~140°F)

OPERATING HUMIDITY

10 ~ 90% @ 40°C, non-condensing

CERTIFICATION

CE/FCC Class A
LVD