




169.00 EUR

incl. 19% VAT, plus [shipping](#)

- Fully motorized !
- Radio
- Amplifier
- DVD Drive !

CARTFT.COM



Support: [Manual \[EN\]](#) | [Connexion diagram \[DE\]](#) | [Connexion diagram \[EN\]](#)

Remnant offer. Refurbished. Slight traces of usage on device. 2 years warranty.

The CID650 Display for the Doppel-DIN-slot has some exiting features :

- Built-In Slot-In DVD drive, which gets connected with your carpc via USB.
- Power- and Reset-button in the front, which can be connected with your carpc.
- The display can be adjusted in height motorized.
- Rear camera sensor cable for automatic switching to rear camera. - Integrated 4x25W amplifier with AM/FM Radio

The CID-650 can be connected to every PC with VGA- and USB connectors.

Drivers-CD included, compatible with :

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,..
- Macintosh OS 9.x, 10.x
- DOS,..

Spezifications

Display size	6.5" digital
Aspect ratio	16:9 wide TFT screen
Dot Resolution	2400x480= 1,152,000 dots
Physical Resolution	800x480
Supported Resolutions	640x480-1024x768
Color configuration	RGB stripe
Power input	DC 11-24V
Power consumption	max. 15W

<i>Video system</i>	2x Video inputs (PAL/NTSC) 1x VGA input
<i>Audio system</i>	- 4x25W Amplifier - AM/FM Radio - 2x AUX input (2x2 Cinch)
	Display Case : 190x176x99 mm Display : 144 x 77 mm Video input signal: 1.0Vp-p, composite video Full function OSD control (englisch)
<i>Scope of Supply</i>	- 6.5" VGA Doppel-DIN Display - IR Remote - ISO-speaker connector cable - ISO-connector cable(Plus,Ignition plus, GND + Rearcam-sensor, PC-Reset, PC-Power) - VGA-cable - USB-cable (for Touchscreen and DVD-drive combined) - 2x Cinch-cables - Touchscreen Driver-CD - Touchscreen pencil - Manual

Manual online : [here](#)

Notes:

- "Brightnness"-Button is without function (by design)