

398.00 EUR  
incl. 19% VAT, plus [shipping](#)

- FANLESS carpc system
- Core2Duo
- Dualchannel VGA
- Intel 945 chipset



CARTFT.COM



Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel Celeron M440 CPU.

| CALU specifications   |                                                                                                                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Processor (supported) | Support Socket 479, FSB 533MHZ, FSB 667MHZ, Intel Mobil CPU (Celeron M 410, 420, 430, 440 & 450 CPU, Core Duo T2300, T2400, T2500, T2600 & T2700 CPU, Core 2 Duo T5500, T5600, T7200, T7400 & T7600 CPU). |
| Memory                | Support 1x SO-DDR-II RAM                                                                                                                                                                                  |
| Chipset               | Intel Intel 945GM / ICH 7M                                                                                                                                                                                |
| Video                 | Intel Graphics Media Accelerator 950                                                                                                                                                                      |
| Audio                 | Software AC '97 Audio CODEC                                                                                                                                                                               |

**Peripheral Connection**

## Front :

1 x IEEE 1394 Firewire port

1 x USB 2.0 / 1.1 Port

1 x MIC Port

1 x Ear Phone output Jack

Power-on button

Reset button

Power-on and HDD LED

## Rear :

1 x RS232 COM port

1 x RJ45 10/100/1000 Mbit Fast Ethernet

1 x Line-Out output Jack

2 x USB 2.0 / 1.1 Ports

1 x 15 pin VGA

1 x DVI

1 x TV-Out

1 x 12v DC Power Jack input

**Storage**

One 2.5 inch SATA Hard Disk

(Support Ultra DMA 33/66/100).

**Weight & Size**

System approximately 3kg (fully equipped).

System Dimension: 155 x 255 x 55 mm

**Power req.**

12V, 5A

**Accessory****Storage**

Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo

Supports all 2.5" SATA IDE hard drive, ATA-100/66/33.

**Scope of supply**

110V/230V EU power supply

Barebone

CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)